SAFETY DATA SHEET		
PROPANE		PETROCANADA
000003000646		
Version 2.1		Revision Date 2018/06/07 Print Date 2018/06/07
SECTION 1. IDENTIFICATION		
Product name	:	PROPANE
Synonyms	:	Propane HD-5, Propane commercial, Liquified Petroleum Gas (LPG), C3H8, CGSB Propane Grade 1, CGSB Propane Grade 2, odorized propane, stenched propane, automotive propane.
Product code	:	100139
Manufacturer or supplier's det	ails	Petro-Canada P.O. Box 2844, 150 - 6th Avenue South-West Calgary Alberta T2P 3E3 Canada
Emergency telephone num- ber		Suncor Energy: +1 403-296-3000; Canutec Transportation: 1-888-226-8832 (toll-free) or 613- 996-6666; Poison Control Centre: Consult local telephone directory for emergency number(s).
Recommended use of the cl	hen	nical and restrictions on use
Recommended use	:	Propane is used as a fuel gas, refrigerant and as a raw mate- rial for organic synthesis. It is also used as a laboratory gas. The grade determines the propane content. It is supplied as pressurized liquid in tanks.
Prepared by	:	Product Safety: +1 905-804-4752

SECTION 2. HAZARDS IDENTIFICATION

Annoaranaa	Coo et reem temperature, liquid when stored under pressure
Appearance	Gas at room temperature; liquid when stored under pressure.,
	Liquefied compressed gas.
Colour	colourless
Odour	Propane is an odourless gas. Odourized propane will contain up
Oddul	
	to 30 g Ethyl Mercaptan per 1000 L of propane.

Emergency Overview

GHS Classification

Flammable gases	: Category 1
Gases under pressure	: Liquefied gas
Simple Asphyxiant	: Category 1

GHS label elements

000003000646



000003000646		
Version 2.1	Revision Date 2018/06/07	Print Date 2018/06/07
Hazard pictograms		
Signal word	: Danger	
Hazard statements	: Extremely flammable gas. Contains gas under pressure; may ex May displace oxygen and cause rapid	
Precautionary statements	 Prevention: Keep away from heat, hot surfaces, so other ignition sources. No smoking. Response: Leaking gas fire: Do not extinguish, us safely. In case of leakage, eliminate all ignition Storage: Protect from sunlight. Store in a well- 	inless leak can be stopped on sources.
Potential Health Effects		
Primary Routes of Entry	: Eye contact Inhalation Skin contact	
Inhalation	: Inhalation may cause central nervous May cause respiratory tract irritation. Inhalation of vapours may cause drow ziness and disorientation.	-
Skin	: Contact with rapidly expanding gas m bite.	ay cause burns or frost-
Eyes	: Contact with rapidly expanding gas m bite.	ay cause burns or frost-
Ingestion	: Exposure by this route unlikely.	
Aggravated Medical Condi- tion	: Overexposure may lead to cardiac se	ensitization.
Other hazards None known.		
IARC	No component of this product present a equal to 0.1% is identified as probable, p human carcinogen by IARC.	
ACGIH	No component of this product present a equal to 0.1% is identified as a carcinog gen by ACGIH.	

000003000646

Version 2.1

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration
propane	74-98-6	90 - 100 %
propylene	115-07-1	1 - 5 %
butane	106-97-8	1 - 2.5 %
ethane	74-84-0	1 - 1.5 %
methane	74-82-8	0.1 - 0.2 %

SECTION 4. FIRST AID MEASURES

If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash contaminated clothing before reuse. Seek medical advice.
In case of eye contact	 Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	: Not a significant route of exposure.
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	e extinguishing measures that nstances and the surroundin	at are appropriate to local cir- g environment.
Unsuitable extinguishing media	information available.	
Specific hazards during fire- fighting	ne product release cannot be oduct to burn itself out. ol closed containers exposed	•

PROPANE

000003000646



Version 2.1	Revision Date 2018/06/07	Print Date 2018/06/07
Hazardous combustion prod- ucts	: Carbon oxides (CO, CO2), smok products of incomplete combustion	0 1
Further information	: Prevent fire extinguishing water f water or the ground water system	5
Special protective equipment for firefighters	: Wear self-contained breathing ap wear. Wear a positive-pressure supplie piece.	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. In case of inadequate ventilation wear respiratory protection. Remove all sources of ignition.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Ensure adequate ventilation. Use explosion-proof ventilation equipment. Non-sparking tools should be used. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap-
	plication area.
	In case of insufficient ventilation, wear suitable respiratory equipment.
	Avoid contact with skin, eyes and clothing. Avoid breathing gas.
	Avoid breating gas. Avoid spark promoters. Ground/bond container and equip- ment. These alone may be insufficient to remove static elec- tricity.
	Use only with adequate ventilation.
	Keep away from heat and sources of ignition.
	Keep container closed when not in use.
	Do not use sparking tools.
	Do not enter areas where used or stored until adequately ven- tilated.
Conditions for safe storage	: Store in original container.
C C	Containers which are opened must be carefully resealed and kept upright to prevent leakage.
	Keep in a dry, cool and well-ventilated place.
	Keep in properly labelled containers.
	To maintain product quality, do not store in heat or direct sun- light.
ternet: www.petro-canada.ca/msds	Page: 4 /

000003000646

PETRO CANADA

Version 2.1

Revision Date 2018/06/07

Print Date 2018/06/07

Keep away from sources of ignition - No smoking. Ensure the storage containers are grounded/bonded.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
propylene	115-07-1	TWA	500 ppm 860 mg/m3	CA AB OEL
		TWA	500 ppm	CA BC OEL
		TWA	500 ppm	ACGIH
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
ethane	74-84-0	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
Engineering measures	Use explosi Adequate v	well-ventilated and on-proof ventilati entilation to ensure ot exceeded.		Exposure

Personal protective equipment

Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	Always wear NIOSH-approved self-contained breathing apparatus when handling this material.
Hand protection Material	:	Wear insulated gloves to prevent frostbite.
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe-
net: www.petro-canada.ca/msds		Page: 5 /

PROPANE



000003000646 Version 2.1 Revision Date 2018/06/07 Print Date 2018/06/07 cific work-place. cific work-place. End of the second second

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Gas at room temperature; liquid when stored under pressure., Liquefied compressed gas.
Colour	:	colourless
Odour	:	Propane is an odourless gas. Odourized propane will contain up to 30 g Ethyl Mercaptan per 1000 L of propane.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	No data available
Boiling point/boiling range	:	-42 °C (-44 °F)
Flash point	:	-104 °C (-155 °F) Method: closed cup
Fire Point	:	No data available
Auto-Ignition Temperature	:	450 °C (842 °F)
Evaporation rate	:	No data available
Evaporation rate Flammability	:	No data available Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considera- ble distance to sources of ignition and flash back. Rapid es- cape of vapour may generate static charge causing ignition. May accumulate in confined spaces.
•		Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considera- ble distance to sources of ignition and flash back. Rapid es- cape of vapour may generate static charge causing ignition.
Flammability	:	Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considera- ble distance to sources of ignition and flash back. Rapid es- cape of vapour may generate static charge causing ignition. May accumulate in confined spaces.
Flammability Upper explosion limit	:	Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considera- ble distance to sources of ignition and flash back. Rapid es- cape of vapour may generate static charge causing ignition. May accumulate in confined spaces. 9.5 %(V)
Flammability Upper explosion limit Lower explosion limit	:	Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considera- ble distance to sources of ignition and flash back. Rapid es- cape of vapour may generate static charge causing ignition. May accumulate in confined spaces. 9.5 %(V) 2.1 %(V)
Flammability Upper explosion limit Lower explosion limit Vapour pressure	:	Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considera- ble distance to sources of ignition and flash back. Rapid es- cape of vapour may generate static charge causing ignition. May accumulate in confined spaces. 9.5 %(V) 2.1 %(V) 10,763 mmHg (38 °C / 100 °F) 1.56
Flammability Upper explosion limit Lower explosion limit Vapour pressure Relative vapour density	:	Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considera- ble distance to sources of ignition and flash back. Rapid es- cape of vapour may generate static charge causing ignition. May accumulate in confined spaces. 9.5 %(V) 2.1 %(V) 10,763 mmHg (38 °C / 100 °F)

PROPANE

000003000646



Version 2.1	Revision Date 2018/06/07	Print Date 2018/06/07
Solubility(ies)		
Water solubility	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Explosive properties	: Do not pressurise, cut, weld, braze pose containers to heat or sources explode in heat of fire. Vapour exp doors or in sewers. Propane may f air.	s of ignition. Containers may losion hazard indoors, out-

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Reactive with oxidising agents and halogenated compounds.
Hazardous decomposition products	:	May release COx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Eye contact Inhalation Skin contact Acute toxicity				
Product:				
Acute oral toxicity	: Remarks: No data available			
Acute inhalation toxicity	: Remarks: No data available			
Acute dermal toxicity	: Remarks: No data available			
<u>Components:</u>				
butane: Acute inhalation toxicity	: LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: gas			

PROPANE

000003000646

Version 2.1



Print Date 2018/06/07

Skin corrosion/irritation

Product:

Remarks: No data available

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	: Remarks: No data available	
Toxicity to daphnia and other aquatic invertebrates	: Remarks: No data available	
Toxicity to algae	: Remarks: No data available	
Toxicity to bacteria	: Remarks: No data available	
Persistence and degradability		

Product:

000003000646

Version 2.1



Print Date 2018/06/07

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of as hazardous waste in compliance with local and national regulations. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR		
UN/ID No.	:	UN 1978
Proper shipping name	:	Propane
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	Class 2 - Gases: Flammable (Division 2.1)
Packing instruction (cargo aircraft)	:	200
IMDG-Code UN number Proper shipping name		UN 1978 PROPANE
Class Packing group Labels EmS Code Marine pollutant	:	2.1 Not assigned by regulation 2.1 F-D, S-U no
Transport in bulk according t	0	Annex II of MARPOL 73/78 and the IBC Co

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

National Regulations

TDG	
UN number	: UN 1978
Proper shipping name	: PROPANE

Marine pollutant

PROPANE

000003000646



000003000040		
Version 2.1	Revision Date 2018/06/07	Print Date 2018/06/07
Class	: 2.1	
Packing group	: Not assigned by regulation	
Labels	: 2.1	
ERG Code	: 115	

: no

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:				
DSL On the inventory, or in compliance with the inventory				
TSCA	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.			
EINECS	On the inventory, or in compliance with the inventory			

SECTION 16. OTHER INFORMATION

For Copy of SDS	:	Internet: www.petro-canada.ca/msds Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837- 1228 For Product Safety Information: 1 905-804-4752
Prepared by	:	Product Safety: +1 905-804-4752
Revision Date	:	2018/06/07

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.